



Creekside Garden Tractor Pullers Association Tech Inspection

2024

5,000 RPM - Class L1 & L2 – 1,150 lb. Both Classes

<u>Safety</u>	<u>Technical</u>
<ul style="list-style-type: none"> <input type="checkbox"/> Secure seat with at least a 3" tall back. <input type="checkbox"/> Engine shutoff switch within driver's reach. <input type="checkbox"/> Pegs and fender straps or boards for feet. <input type="checkbox"/> Rear fenders 4" horizontal over rear tires. <input type="checkbox"/> Wide front axles with adequate steering. Tracking within rear wheels. <input type="checkbox"/> Functioning rear brakes. <input type="checkbox"/> Capable drawbar. <input type="checkbox"/> Weights secured & free of sled chain. <input type="checkbox"/> 360° shield around clutch(s). <input type="checkbox"/> 360° shield around flywheel. <input type="checkbox"/> Shielded belt, chain, pulley, drive shaft. <input type="checkbox"/> U-joints shielded 360°. <input type="checkbox"/> Exhaust discharges safely. Not towards side, front, or sled operator. <input type="checkbox"/> Safe throttle control system. Non-stock has a return spring. Hand throttles push forward. <input type="checkbox"/> Safe and secured fuel system. Lines routed safely. <input type="checkbox"/> Batteries secured and protected. <input type="checkbox"/> Capable wheelie bars with bumpers. <input type="checkbox"/> Working pull-out type safety tether switch. <input type="checkbox"/> DOT approved helmet with full face shield and fire jacket with long cotton pants. Footwear. <input type="checkbox"/> Fire extinguisher. <p style="text-align: center; font-style: italic; font-size: small;">CGTPA strives to maintain the spirit of "good sportsmanship". Investing club resources to prove that you are legal impedes this effort. CGTPA reserves the right to move you to another class if we feel you are exceeding the restrictions of this class. Fire Extinguisher required.</p>	<p style="text-align: center;">Chassis</p> <ul style="list-style-type: none"> <input type="checkbox"/> OEM frame and chassis combination in the OEM locations. <input type="checkbox"/> Stock or fabricated front axle up to 56" wheelbase. Measured wheelbase is _____ inches. <input type="checkbox"/> Weights <= 24" rearward and <= 96" forward of rear axle centerline. Extended weight measurement is _____ inches. <input type="checkbox"/> Hitch height 13" max. <p style="text-align: center;">Tires</p> <ul style="list-style-type: none"> <input type="checkbox"/> Ag, Pro Molded or Cut Tires <input type="checkbox"/> Max size 26-12.00 x 12 on a max 12" rim. <p style="text-align: center;">Drivetrain</p> <ul style="list-style-type: none"> <input type="checkbox"/> Garden tractor type rear-end, differential, or transaxle. OEM type. <input type="checkbox"/> Must have clutch shielding of .125 steel or .250 aluminum. <p style="text-align: center;">Engines</p> <ul style="list-style-type: none"> <input type="checkbox"/> Factory or OEM manufactured garden tractor engines only. <input type="checkbox"/> Internal modifications allowed. .030" max. overbore. <input type="checkbox"/> Aftermarket carburetor, ignition, cylinder heads, steel flywheel, starters allowed. <input type="checkbox"/> Must run a governor & limited to 5,000 RPM. Measured RPM _____ <input type="checkbox"/> Attached dedicated starter. No starter cart. <input type="checkbox"/> Flywheel shielding of 0.125" steel or 0.250" aluminum. <input type="checkbox"/> 25hp or less. Model: _____ HP: _____

Driver/Owner:	
Tractor No:	
Date:	
Inspected by:	Approved for 1 event