



Creekside Garden Tractor Pullers Association Tech Inspection

2024

Mini Rod - Classes T & U – 1,950 lb. Both Classes

<u>Safety</u>	<u>Technical</u>
<ul style="list-style-type: none"> <input type="checkbox"/> Secure seat with 6" tall back. <input type="checkbox"/> Engine shutoff switch within driver's reach. <input type="checkbox"/> Pegs and fender straps or boards for feet. <input type="checkbox"/> Wide front axles with adequate steering. Tracking within rear wheels. <input type="checkbox"/> Functioning rear brakes <input type="checkbox"/> Capable drawbar with minimum 1" solid grade 8 bolt attaching it to the tractor. <input type="checkbox"/> Weights secured & free of sled chain. <input type="checkbox"/> Shielded belt, chain, pulley, drive shaft. <input type="checkbox"/> U-joints shielded 360°. <input type="checkbox"/> Exhaust discharges safely. Not towards side, front, or sled operator. <input type="checkbox"/> Safe throttle control system with spring return to neutral. Hand throttles push forward. <input type="checkbox"/> Batteries secured and protected. <input type="checkbox"/> Capable wheelie bars with bumpers. <input type="checkbox"/> Working tether tested with "pull test" running or buzz box <u>each event</u>, NOTE: tether must kill both engine and fuel pump when pulled. <input type="checkbox"/> DOT approved helmet with full face shield and fire jacket with long cotton pants. Footwear. <input type="checkbox"/> 2" backup light when in reverse. <input type="checkbox"/> Safety neutral switch. <input type="checkbox"/> 2 ½ lb. fire extinguisher within easy reach. <p style="text-align: center; font-style: italic; font-size: small;">CGTPA strives to maintain the spirit of "good sportsmanship". Investing club resources to prove that you are legal impedes this effort. CGTPA reserves the right to move you to another class if we feel you are exceeding the restrictions of this class. Fire Extinguisher required.</p>	<p style="text-align: center; font-weight: bold; margin-bottom: 10px;">Chassis</p> <ul style="list-style-type: none"> <input type="checkbox"/> Sheet metal is optional except for barrier between driver and tires. <input type="checkbox"/> Max. forward length is 96" from rear axle centerline. Measure length is _____ inches. <input type="checkbox"/> 72" max. tractor width. Measured width is _____ inches. <input type="checkbox"/> Roll cage & minimum 4-point harness. <input type="checkbox"/> Max. hitch height 13" <p style="text-align: center; font-weight: bold; margin-bottom: 10px;">Tires</p> <ul style="list-style-type: none"> <input type="checkbox"/> Max. size 18.4 x 16.1 <input type="checkbox"/> Pneumatic tires - no studs, chains, or duals. <p style="text-align: center; font-weight: bold; margin-bottom: 10px;">Drivetrain</p> <ul style="list-style-type: none"> <input type="checkbox"/> SEMA approved bellhousing only. <input type="checkbox"/> No cast iron flywheel. <input type="checkbox"/> Transmissions may be OEM equipment or aftermarket quick change gear box covered with approved blanket or scatter shield. <input type="checkbox"/> Driveshaft covered 360° with .250" steel or .375" aluminum. <input type="checkbox"/> Fans & harmonic balancers min. .0625" steel or .125" aluminum shielding. <p style="text-align: center; font-weight: bold; margin-bottom: 10px;">Engines</p> <ul style="list-style-type: none"> <input type="checkbox"/> Max. 420 CID, naturally aspirated, internal combustion, cast iron block. <input type="checkbox"/> No roller cams or lifters, offset lifters, or mushroom lifters. <input type="checkbox"/> Two valves and one sparkplug per cylinder. <input type="checkbox"/> Carburetor(s) limited to 4 venturis. <input type="checkbox"/> Engine side shields 6" above and below crankshaft centerline. .0625 steel or .125 aluminum. <input type="checkbox"/> <u>Water</u> cooling overflow jug or into exhaust. <input type="checkbox"/> Gasoline only.

Driver/Owner:	
Tractor No:	
Date:	
Inspected by:	Approved for 1 event