

Creekside Garden Tractor Pullers Association Tech Inspection

2024

Stock Single - Classes F, G, H & F-EFI, G-EFI, H-EFI 950 lb., 1,050 lb. & 1,150lb.

<u>Safety</u>	<u>Technical</u>
 Secure seat with at least a 3" tall back. Engine shutoff switch within driver's reach. Pegs and fender straps or boards for feet. Rear fenders 4" horizontal over rear tires. Wide front axles with adequate steering.	Chassis Any OEM frame and chassis combinations. OEM or fabricated front axle up to 56" wheelbase. Measured wheelbase is inches. Weights <= 24" rearward or <= 96" forward of rear axle centerline. Extended weight measurement is inches. Hitch height 13" Max. Tires Ag, molded, or cut tires. Max size 26-12.00 x 12 with max. rim 12". Drivetrain Garden Tractor type rear-end, differential, or transaxle. OEM type. Engines Factory or OEM garden tractor engines only. No internal modifications except .030 overbore. Stock carburetor. EFI. OEM EFI run in EFI class. Stock engine block, camshaft, cylinder heads, and start. No start cart. Must run a governor & limited to 4,200 RPM. Measured RPM: Gasoline only. Single cylinder, 16hp or less. Engine Model: HP:
Driver/Owner:	
Tractor No:	
Date:	
Inspected by:	Approved for 1 event