

Stock Twin - Classes I, J, K & I-EFI, J-EFI, K-EFI 950 lb., 1,050 lb. & 1,150lb.

<u>Safety</u>	<u>Technical</u>
 Secure seat with at least a 3" tall back. Engine shutoff switch within driver's reach. Pegs and fender straps or boards for feet. Rear fenders 4" horizontal over rear tires. Wide front axles with adequate steering.	Chassis Any OEM frame and chassis combinations. OEM or fabricated front axle up to 56"
Tracking within rear wheels. Functioning rear brakes. Capable drawbar. Weights secured & free of sled chain. 360° shield around clutch(s). Shielded belt, chain, pulley, drive shaft. U-joints shielded 360°. Exhaust discharges safely. Not towards side, front, or sled operator. Safe throttle control system. Non-stock has a return spring. Hand throttles push forward. Safe and secured fuel system. Lines routed safely. Batteries secured and protected. Capable wheelie bars with bumpers. Working pull-out type safety tether switch. DOT helmet with full face shield or appropriate eye protection. Long cotton pants and long sleeve shirt. Footwear. Fire extinguisher. <i>CGTPA strives to maintain the spirit of "good sportsmanship". Investing club resources to prove that you are legal impedes this effort. CGTPA reserves the right to move you to another class if we feel you are exceeding the restrictions of this class. Fire Extinguisher required.</i>	wheelbase. Measured wheelbase is

Driver/Owner:	
Tractor No:	
Date:	
Inspected by:	Approved for 1 event