



Creekside Garden Tractor Pullers Association Tech Inspection

2024

Pro Stock & Super Stock Diesel - Classes N & O 1,200 lbs.

<u>Safety</u>	<u>Technical</u>
<ul style="list-style-type: none"> <input type="checkbox"/> Secure seat with at least a 3" tall back. <input type="checkbox"/> Engine shutoff switch within driver's reach. <input type="checkbox"/> Pegs and fender straps or boards for feet. <input type="checkbox"/> Rear fenders 4" horizontal over rear tires. <input type="checkbox"/> Wide front axles with adequate steering. Tracking within rear wheels. <input type="checkbox"/> Functioning rear brakes. <input type="checkbox"/> Capable drawbar. <input type="checkbox"/> Weights secured & free of sled chain. <input type="checkbox"/> 360° shield around clutch(s). <input type="checkbox"/> Shielded belt, chain, pulley, drive shaft. <input type="checkbox"/> U-joints shielded 360°. <input type="checkbox"/> Exhaust discharges safely. Not towards side, front, or sled operator. <input type="checkbox"/> Safe throttle control system. Non-stock has a return spring. Hand throttles push forward. <input type="checkbox"/> Safe and secured fuel system. Lines routed safely. <input type="checkbox"/> Batteries secured and protected. <input type="checkbox"/> Capable wheelie bars with bumpers. <input type="checkbox"/> Working pull-out type safety tether switch. <input type="checkbox"/> Turbo and supercharger shielded 360° and must have fragment bolts in exhaust. <input type="checkbox"/> DOT helmet with full face shield and fire jacket with long cotton pants. Footwear. <input type="checkbox"/> Fire extinguisher. <p style="text-align: center; font-style: italic;">CGTPA strives to maintain the spirit of "good sportsmanship". Investing club resources to prove that you are legal impedes this effort. CGTPA reserves the right to move you to another class if we feel you are exceeding the restrictions of this class. Fire Extinguisher required.</p>	<p style="text-align: center;">Chassis</p> <ul style="list-style-type: none"> <input type="checkbox"/> OEM appearing with any original hood, grill, and frame. <input type="checkbox"/> Weights <= 24" rearward or <= 96" forward of rear axle centerline. Extended weight measurement is _____ inches. <input type="checkbox"/> Hitch height 13" Max. <p style="text-align: center;">Tires</p> <ul style="list-style-type: none"> <input type="checkbox"/> Ag, molded, or cut tires. <input type="checkbox"/> Max size 26-12.00 x 12 <p style="text-align: center;">Drivetrain</p> <ul style="list-style-type: none"> <input type="checkbox"/> Drivetrain components must be original, internal modifications allowed. <p style="text-align: center;">Engines</p> <ul style="list-style-type: none"> <input type="checkbox"/> Limited to one 4 cycle garden tractor engine. <input type="checkbox"/> Maximum 3 cylinders and 70 CID diesel or 48 CID on gas. <input type="checkbox"/> Gasoline or diesel fuel only. (water injection permitted for diesel) <input type="checkbox"/> OHV or OHC must retain stock heads and valves. <input type="checkbox"/> No modifications to engine block. <input type="checkbox"/> Steel flywheel required. <input type="checkbox"/> Diesels have stock injectors and pump. <input type="checkbox"/> Single turbocharger allowed on diesels only. <input type="checkbox"/> Supercharger permitted in place of turbo. <input type="checkbox"/> Stock stroke and maximum .040" overbore. <input type="checkbox"/> Reground camshaft on original core. <input type="checkbox"/> One carburetor per cylinder or one two-barrel carburetor. Max. venturi 1.200" or 30 mm <input type="checkbox"/> OEM rotating mass in stock classes. <input type="checkbox"/> Billet steel or aluminum starting pulleys. <input type="checkbox"/> Non-stocks, engine side shields. <input type="checkbox"/> Starting or timing pulleys pinned into crank.

Driver/Owner:	
Tractor No:	
Date:	
Inspected by:	Approved for 1 event