

Super Stock - Class M – 1,050lb.			
<u>Safety</u>	<u>Technical</u>		
 Secure seat with at least a 3" tall back. Engine shutoff switch within driver's reach. Pegs and fender straps or boards for feet. Rear fenders 4" horizontal over rear tires. Wide front axles with adequate steering. Tracking within rear wheels. Functioning rear brakes. Capable drawbar. Weights secured & free of sled chain. 360° shield around clutch(s). 360° shield around flywheel. Shielded belt, chain, pulley, drive shaft. U-joints shielded 360°. Exhaust discharges safely. Not towards side, front, or sled operator. Safe throttle control system. Non-stock has a return spring. Hand throttles push forward. Safe and secured fuel system. Lines routed safely. Batteries secured and protected. Capable wheelie bars with bumpers. Working pull-out type safety tether switch. DOT approved helmet with full face shield and fire jacket with long cotton pants. Footwear. Fire extinguisher. <i>CGTPA strives to maintain the spirit of "good sportsmanship". Investing club resources to prove that you are legal impedes this effort. CGTPA reserves the right to move you to another class if we feel you are exceeding the restrictions of this class. Fire Extinguisher required.</i> 	Chassis OEM appearing with any original hood, grill, and frame. From an OEM produce garden tractor. May be lengthened. Weights <= 24" rearward or <= 96" forward of rear axle centerline. Extended weight measurement is inches.		

Owner:	Driver/Owner:	
tor No:	Tractor No:	
Date:	Date:	
ted by: Approved for 1	Inspected by:	/ed for 1 event